

Debian 13 aka. Trixie

Fixes

- [Stromverbrauch im Schlafmodus mit einer Samsung 990 Evo NVMe](#)

```
sudo su
nano /etc/default/grub
# Zeile die mit [GRUB_CMDLINE_LINUX_DEFAULT=] beginnt finden und
[nvme.noacpi=1] zu den bestehenden Parametern hinzufügen
GRUB_CMDLINE_LINUX_DEFAULT="quiet splash nvme.noacpi=1"
#
update-grub
```

System-Tools

.desktop

Quellen:

- <https://wiki.ubuntuusers.de/.desktop-Dateien/>
- <https://specifications.freedesktop.org/desktop-entry-spec/latest/example.html>



Restart des laufenden Desktops:

Bei GNOME geht das mit den Tasten Alt + F2 , und dann ein kleines R eingeben und mit ↵ abschließen.

Beispiel *.desktop Datei:

[org.freecad.FreeCAD.desktop](#)

```
[Desktop Entry]
Name=FreeCAD
Comment=Feature-basierter parametrischer Modellierer
GenericName=CAD Application
Exec=/usr/bin/flatpak run --branch=stable --arch=x86_64 --
command=FreeCAD --file-forwarding org.freecad.FreeCAD - --single-
instance @@ %F @@
Icon=/home/christoph/.icons/FreeCAD_Logo.svg
Terminal=false
Type=Application
Icon=org.freecad.FreeCAD
Categories=Development;Engineering;
StartupNotify=true
```

```
StartupWMClass=FreeCAD
MimeType=application/x-extension-
fcstd;model/obj;image/vnd.dwg;image/vnd.dxf;model/vnd.collada+xml;appli
cation/iges;model/iges;model/step;model/step+zip;model/stl;application/
vnd.shp;model/vrml;
X-Flatpak=org.freecad.FreeCAD
Hidden=false
NoDisplay=false
```

```
mv org.freecad.FreeCAD.desktop ~/.local/share/applications
wget https://upload.wikimedia.org/wikipedia/commons/1/1a/FreeCAD-symbol.svg
-o FreeCAD_Logo.svg
mv FreeCAD_Logo.svg ~/.icons/
```

```
#Window Class ermitteln:
xprop WM_CLASS
# Dann "klick" auf die Titelleiste des unbekannten Fensters

# Validate *.desktop files
desktop-file-validate ~/.local/share/applications/<MYFILE>.desktop
```

Systembasis

- [TUXEDO Software-Paketquellen hinzufügen](#)

```
wget -O - https://deb.tuxedocomputers.com/0x54840598.pub.asc | gpg --dearmor
| sudo tee /usr/share/keyrings/tuxedo-archive-keyring.gpg > /dev/null
wget https://deb.tuxedocomputers.com/0x54840598.pub.asc
mv 0x54840598.pub.asc tuxedo-archive-keyring.gpg
cp tuxedo-archive-keyring.gpg /etc/apt/trusted.gpg.d/
#
apt-get install tuxedo-control-center
apt-get install tuxedo-drivers
apt-get install tuxedo-tomte-light
```

```
# deb cdrom:[Debian GNU/Linux 13.0.0 _Trixie_ - Official amd64 NETINST with
firmware 20250809-11:20]/ trixie contrib main non-free-firmware
```

```
deb https://debian.tu-bs.de/debian/ trixie main contrib non-free non-free-
firmware
deb-src https://debian.tu-bs.de/debian/ trixie main contrib non-free non-
free-firmware
```

```
deb https://security.debian.org/debian-security/ trixie-security main
contrib non-free non-free-firmware
deb-src https://security.debian.org/debian-security/ trixie-security main
contrib non-free non-free-firmware
```

```
# trixie-updates, to get updates before a point release is made;
# see
https://www.debian.org/doc/manuals/debian-reference/ch02.en.html#_updates_and_backports
deb https://debian.tu-bs.de/debian/ trixie-updates main contrib non-free non-free-firmware
deb-src https://debian.tu-bs.de/debian/ trixie-updates main contrib non-free non-free-firmware

# This system was installed using removable media other than
# CD/DVD/BD (e.g. USB stick, SD card, ISO image file).
# The matching "deb cdrom" entries were disabled at the end
# of the installation process.
# For information about how to configure apt package sources,
# see the sources.list(5) manual.

deb https://deb.tuxedocomputers.com/debian trixie main
```

apt-get update && apt-get dist-upgrade

```
apt-get install mc synaptic aptitude cifs-utils ca-certificates davfs2
libfuse2t64 gocryptfs gparted cryptmount partitionmanager putty dosfstools
mtools fatcat fatresize curl gedit gnome-tweaks dconf-editor gnome-tweaks
nemo nemo-data nemo-fileroller nemo-compare nemo-python yaru-theme-icon
yaru-theme-gnome-shell yaru-theme-unity gnome-icon-theme gnome-brave-icon-theme
gnome-commander rsync gnome-firmware dos2unix network-manager-openvpn-gnome
openvpn-systemd-resolved network-manager-vpnc-gnome
```



Paket-Datenbank neu aufbauen:
`sudo rm /var/lib/apt/lists/*`
`sudo apt update`

Nützliche Werkzeuge

```
apt-get install openjdk-21-jdk kdiff3 krename qtqr mediainfo mediainfo-gui
texlive texlive-lang-german texlive-latex-extra texmaker sqlitebrowser
```

Caja

Caja ist die Nemo Alternative aus der Linux-Mint Welt



su

```
apt-get install caja caja-actions caja-actions-common caja-common caja-
extensions-common caja-image-converter caja-mediainfo caja-open-terminal
caja-rename
```

User -> "sudo"

```
su -  
usermod -aG sudo <username>  
echo "<username> ALL=(ALL:ALL) ALL" >> /etc/sudoers
```

GoCryptFS

Zum Einbinden mit GoCryptFs verschlüsselter Verzeichnisse muss der Parameter „user_allow_other“ in der Datei /etc/fuse.conf eingetragen sein:

```
su  
echo "user_allow_other" >> /etc/fuse.conf
```

Konfiguration

```
# init and use it:  
mkdir ~/.gocryptfs ~/Chr_decrypt  
gocryptfs -init ~/.gocryptfs
```

Autostart@Login

```
cp ./local/share/applications/MyMounts.desktop ./config/autostart/  
chmod +x ./config/autostart/MyMounts.desktop  
# disable the following lines by adding '#':  
# #Actions=...  
# #[Desktop ...  
# #Name= ...
```

Flatpak installieren und aktivieren



Flatpak ist eine Sandbox-Umgebung, d.h jede darin installierte Applikation läuft für sich (gekapselt) und hat, ohne Änderungen der Konfiguration (siehe Flatseal), keinen Zugriff auf z.B. Systemdienste, Geräte, oder das Home-Verzeichnis.

```
su  
apt-get update && apt-get dist-upgrade  
apt-get install flatpak gnome-software-plugin-flatpak  
flatpak remote-add --if-not-exists flathub  
https://dl.flathub.org/repo/flathub.flatpakrepo
```

[Flatpak Pakete suchen](#)

[Flatpak Doku](#)



Installierte Flatpak Pakete anzeigen: `flatpak list`
 Pakete entfernen: `flatpak uninstall org.mozilla.Thunderbird`

Flatseal

Individuelles Rechte-Management mit Flatseal:

```
flatpak install flathub com.github.tchx84.Flatseal
```



Flatseal legt individuelle Konfigurationen unter
`~/.local/share/flatpak/overrides/<Paketname>` ab.

WebDAV

```
su -  
usermod -aG davfs2 <benutzername>
```

KeepassXC

```
flatpak install flathub org.keepassxc.KeePassXC
```

GNOME Shell Erweiterungen

Unterstützung für GNOME Shell Erweiterungen installieren:

```
apt-get install gnome-shell gnome-shell-common gnome-shell-extension-apps-  
menu gnome-shell-extension-auto-move-windows gnome-shell-extensions gnome-  
shell-extension-desktop-icons-ng gnome-shell-extension-drive-menu gnome-  
shell-extension-gpaste gnome-shell-extension-launch-new-instance gnome-  
shell-extension-light-style gnome-shell-extension-manager gnome-shell-  
extension-native-window-placement gnome-shell-extension-places-menu gnome-  
shell-extension-prefs gnome-shell-extension-screenshot-window-sizer gnome-  
shell-extension-status-icons gnome-shell-extension-system-monitor gnome-  
shell-extension-tiling-assistant gnome-shell-extension-user-theme gnome-  
shell-extension-window-list gnome-shell-extension-windows-navigator gnome-  
shell-extension-workspace-indicator gnome-shell-extensions gnome-shell-  
extensions-common gnome-shell-extensions-extra yaru-theme-gnome-shell gnome-  
browser-connector gnome-extra-icons
```

Via Erweiterungs-Manager (gnome-shell-extension-manager) folgende GNOME Shell Erweiterungen installieren:

- Apps Menu
- Bluetooth Battery Meter
- Dash to Dock (by michele_g)
- Desktop Icons NG (DING) (by rastersof)
- Edit Desktop Files (.desktop)
- GSConnect (by dlandau)
- Lock Keys (by kazimieras.vaina)
- Net speed Simplified (by Prateek SU)
- Open Bar (by x10shun)
- Places Status Indicator
- Quick Settings Audio Panel
- Removable Drive Menu/
- Simple net speed (by bijignom) inkompatibel, 08/2025
- System Monitor (by fmuellner)
- Top Bar Organizer (zum Verschieben der LAN IP Anzeige in den linken Bereich)
- User Themes
- Just Perfection (by JustPerfection)

Pimp my Desktop - Conky

- <https://github.com/brndnmtthws/conky>
- conky.cc

```
cat .conkyrc
-- Conky, a system monitor https://github.com/brndnmtthws/conky
--
-- This configuration file is Lua code. You can write code in here, and it
will
-- execute when Conky loads. You can use it to generate your own advanced
-- configurations.
--
-- Try this (remove the `--`):
--
--   print("Loading Conky config")
--
-- For more on Lua, see:
-- https://www.lua.org/pil/contents.html
--
-- Conky Lua API: https://conky.cc/lua
--
-- Configuration settings: https://conky.cc/config_settings
conky.config = {
    alignment = 'middle_right',
    background = false,
    border_width = 1,
    cpu_avg_samples = 2,
```

```
default_bar_height = 6,
default_color = 'white',
default_outline_color = 'white',
default_shade_color = 'white',
double_buffer = true,
draw_borders = false,
draw_graph_borders = true,
draw_outline = false,
draw_shades = false,
extra_newline = false,
font = 'DejaVu Sans Mono:size=11',
format_human_readable = true,
gap_x = 20,
gap_y = 0,
minimum_height = 5,
minimum_width = 400,
net_avg_samples = 2,
no_buffers = true,
out_to_console = false,
out_to_ncurses = false,
out_to_stderr = false,
out_to_wayland = false,
out_to_x = true,
own_window = true,
own_window_class = 'Conky',
own_window_type = 'normal',
own_window_transparent = true,
own_window_argb_visual = true,
own_window_argb_value = 145,
own_window_hints = 'undecorated,sticky,below,skip_taskbar,skip_pager',
show_graph_range = false,
show_graph_scale = true,
short_units = true,
stippled_borders = 0,
update_interval = 1.0,
uppercase = false,
use_spacer = 'none',
use_xft = true,

--Colours
-- default_color = '#D9FFE2',
color1 = '#FF0000',      --red
color2 = '#3E5570',      --grey/blue
color3 = '#CCCCCC',      --grey
color4 = '#BBBBBB',      --grey
color5 = '#C0FF00',      --light green
color6 = '#FFFFFF',      --white

--Signal Colours
color7 = '#C0FF00',      --light green
color8 = '#FFA726',      --orange
```

```
        color9 = '#F1544B',          --firebrick
    }

-- Variables: https://conky.cc/variables
conky.text = [[
${color6}${font Roboto:size=30}${alignc}${time %H}:${time %M}${font}
${color6}${font Roboto:size=15}${alignc}${time %A}, ${time %e} ${time %B}
${time %Y}${font}

${color6}${font Roboto:style=Bold:size=15}S Y S T E M ${hr 2}${font}
${color grey}OS: ${distribution} $sysname
${color grey}Kernel: ${kernel} ${sysname}
${color grey}Uptime:${color} $uptime

${color6}${font Roboto:style=Bold:size=15}C P U ${hr 2}${font}
${color grey}Frequency (in GHz):${color} $freq_g
${color grey}CPU   1 usage:${color} ${cpu cpu1} ${cpubar cpu1}
${color grey}CPU   2 usage:${color} ${cpu cpu2} ${cpubar cpu2}
${color grey}CPU   3 usage:${color} ${cpu cpu3} ${cpubar cpu3}
${color grey}CPU   4 usage:${color} ${cpu cpu4} ${cpubar cpu4}
${color grey}CPU   5 usage:${color} ${cpu cpu5} ${cpubar cpu5}
${color grey}CPU   6 usage:${color} ${cpu cpu6} ${cpubar cpu6}
${color grey}CPU   7 usage:${color} ${cpu cpu7} ${cpubar cpu7}
${color grey}CPU   8 usage:${color} ${cpu cpu8} ${cpubar cpu8}
${color grey}CPU   9 usage:${color} ${cpu cpu9} ${cpubar cpu9}
${color grey}CPU  10 usage:${color} ${cpu cpu10} ${cpubar cpu10}
${color grey}CPU  11 usage:${color} ${cpu cpu11} ${cpubar cpu11}
${color grey}CPU  12 usage:${color} ${cpu cpu12} ${cpubar cpu12}

${color6}${font Roboto:style=Bold:size=15}M E M O R Y ${hr 2}${font}
${color grey}RAM Usage:${color} $mem / $memmax - $memperc% ${membar 4}
${color grey}Swap Usage:${color} $swap / $swapmax - $swapper% ${swapbar 4}

${color6}${font Roboto:style=Bold:size=15}F I L E   S Y S T E M ${hr
2}${font}
/: ${color}${fs_used /} / ${fs_size /} ${fs_bar 6 /}
/home: ${color}${fs_used /home} / ${fs_size /home} ${fs_bar 6 /home}

${color6}${font Roboto:style=Bold:size=15}B A T T E R Y ${hr 2}${font}
${color grey}Power Consumption: ${battery_power_draw} W
${color grey}State: ${battery_status}, Runtime: ${battery_time}
${color grey}Capacity: ${battery_percent}% ${battery_bar}

${color6}${font Roboto:style=Bold:size=15}P R O C E S S E S ${hr 2}${font}
${color grey}Processes:${color} $processes  ${color grey}Running:${color}
$running_processes
$hr
${color grey}Name          PID      CPU%    MEM%
${color lightgrey} ${top name 1} ${top pid 1} ${top cpu 1} ${top mem 1}
```



```

${color lightgrey} ${top name 2} ${top pid 2} ${top cpu 2} ${top mem 2}
${color lightgrey} ${top name 3} ${top pid 3} ${top cpu 3} ${top mem 3}
${color lightgrey} ${top name 4} ${top pid 4} ${top cpu 4} ${top mem 4}
${if_up wlo1}
${color6}${font Roboto:style=Bold:size=15}N E T W O R K  ${hr 2}${font}
${color6}Internal IP Address:${color}${alignr}${addrs wlo1}
${color6}Default Gateway:${color}${alignr}${gw_ip}
${color6}External IP Address:${color}${alignr}${texeci 3600 wget -q -O-
https://ipecho.net/plain}
${color6}WLAN SSID: ${alignr}${wireless_essid wlo1}
${color6}WLAN Frequency: ${alignr}${wireless_freq wlo1}
${color6}WLAN Bitrate: ${alignr}${wireless_bitrate wlo1}
${color6}WLAN Link Quality: ${alignr}${wireless_link_qual_perc wlo1}%
${color6}Network Speed (Up/Down):${color}${alignr}${upspeed wlo1} /
${downspeed wlo1}
${color6}Upload / Download Total:${color}${alignr}${totalup wlo1} /
${totaldown wlo1}
${upspeedgraph wlo1 35, 400 ff0000 00ff00 100000000 -t -l}
${downspeedgraph wlo1 35, 400 ff0000 00ff00 100000000 -t -l}
${endif}

${if_up enx00e04c6808e4}
${color6}${font Roboto:style=Bold:size=15}N E T W O R K  ${hr 2}${font}
${color6}Internal IP Address:${color}${alignr}${addrs enx00e04c6808e4}
${color6}Default Gateway:${color}${alignr}${gw_ip}
${color6}External IP Address:${color}${alignr}${texeci 3600 wget -q -O-
https://ipecho.net/plain}
${color6}WLAN SSID: ${alignr}${wireless_essid enx00e04c6808e4}
${color6}WLAN Frequency: ${alignr}${wireless_freq enx00e04c6808e4}
${color6}WLAN Bitrate: ${alignr}${wireless_bitrate enx00e04c6808e4}
${color6}WLAN Link Quality: ${alignr}${wireless_link_qual_perc
enx00e04c6808e4}%
${color6}Network Speed (Up/Down):${color}${alignr}${upspeed enx00e04c6808e4}
/ ${downspeed enx00e04c6808e4}
${color6}Upload / Download Total:${color}${alignr}${totalup enx00e04c6808e4}
/ ${totaldown enx00e04c6808e4}
${upspeedgraph enx00e04c6808e4 35, 400 ff0000 00ff00 100000000 -t -l}
${downspeedgraph enx00e04c6808e4 35, 400 ff0000 00ff00 100000000 -t -l}
${endif}
]]

```

Yubico Authenticator

```
flatpak install flathub com.yubico.yubioath
```

Nitrokey

```
sudo add-apt-repository ppa:nitrokey/nitrokey
```

```
sudo apt install nitrokey-app
#
flatpak install flathub com.nitrokey.nitrokey-app2
```

AusweisApp2



Konfig-Datei liegt unter:
~/.var/app/de.bund.ausweisapp.ausweisapp2/config/flathub/AusweisA
pp2.conf

```
flatpak install flathub de.bund.ausweisapp.ausweisapp2
```

KDE ISO Imager

Warpinator

```
flatpak install flathub org.x.Warpinator
```

FileZilla



Konfig-Datei liegt unter:
~/.var/app/org.filezillaproject.Filezilla/config/filezilla/
Die Flatpak Konfig liegt hier:
~/.local/share/flatpak/overrides/org.filezillaproject.Filezilla

```
flatpak install flathub org.filezillaproject.Filezilla
```

[org.filezillaproject.Filezilla](#)

```
[Context]
sockets=!ssh-auth
filesystems=home
```

Office und Internet

Brother HL-3170CDW Farblaserdrucker

Quelle: <https://www.brother.de/support/hl-3170cdw/downloads>

```
cd Downloads
wget https://download.brother.com/welcome/dlf006893/linux-brprinter-
installer-2.2.6-0.gz
gunzip linux-brprinter-installer-2.2.6-0.gz
chmod +x linux-brprinter-installer-2.2.6-0
sudo su
./linux-brprinter-installer-2.2.6-0 HL-3170CDW
```

Drucker über CUPS hinzufügen und konfigurieren:


<http://localhost:631/>

- **Verwaltung** -> **Drucker hinzufügen** -> LPD/LPR-Host oder -Drucker -> **Weiter**
- **Verbindung:** -> lpd://192.168.100.8/BINARY_P1 -> **Weiter**
- **Name:** -> Brother_HL3170CDW, **Beschreibung** -> Farblaserdrucker, **Ort** -> Büro -> **Weiter**
- **Hersteller** -> BROTHER -> **Weiter**
- **Modell:** -> Brother HL-3170CDW -> **Drucker hinzufügen**

Firefox

```
flatpak install flathub org.mozilla.firefox
```

Anschließend via Flatseal das Home-Verzeichnis zugänglich machen:



Oder alternativ:

```
cd ~
echo -e '[Context]\ndevices=dri\nfilesystems=home' >>
.local/share/flatpak/overrides/org.mozilla.firefox
```

Benutzerdefinierte Tabs: ~/.mozilla/firefox/<PROFILE-FOLDER>/chrome/userChrome.css

userChrome.css

```
/* Optional: Zusätzlicher Abstand zwischen den Tabs */
.tabbrowser-tab + .tabbrowser-tab {
    margin-top: -6px !important; /* oder ein anderer gewünschter
Abstand */
}

#TabsToolbar {
    --tab-min-height: 20px; /* Passen Sie diesen Wert an (z.B. 40px,
50px) */
    --tab-max-height: 20px;
}

#tabbrowser-tabs {
    --tab-min-height: 20px; /* Gleicher Wert wie oben */
    --tab-max-height: 20px;
}
```

Video Downloadhelper

```
# Companion App herunterladen:
# https://github.com/aclap-dev/video-downloadhelper/wiki/CoApp-Installation
wget https://github.com/aclap-dev/vdhcoapp/releases/latest/download/vdhcoapp-linux-x86\_64.deb
sudo dpkg -i vdhcoapp-linux-x86_64.deb
/opt/vdhcoapp/vdhcoapp install # (not as root! Don't use sudo)
Installing...
Flatpak is installed. Making the coapp available from browser sandboxes:
Linked coapp within org.mozilla.firefox.
Linked coapp within com.brave.Browser.
Linked coapp within com.google.Chrome.
Linked coapp within com.google.ChromeDev.
Linked coapp within org.chromium.Chromium.
Linked coapp within com.github.Eloston.UngoogledChromium.
Linked coapp within com.microsoft.Edge.
Linked coapp within com.microsoft.EdgeDev.
Writing /home/christoph/.mozilla/native-messaging-
hosts/net.downloadhelper.coapp.json
Writing /home/christoph/.var/app/org.mozilla.firefox/.mozilla/native-
messaging-hosts/net.downloadhelper.coapp.json
Writing /home/christoph/.config/google-
chrome/NativeMessagingHosts/net.downloadhelper.coapp.json
Writing
/home/christoph/.config/chromium/NativeMessagingHosts/net.downloadhelper.coa
pp.json
Writing /home/christoph/.config/BraveSoftware/Brave-
Browser/NativeMessagingHosts/net.downloadhelper.coapp.json
```


```
Writing /home/christoph/.var/app/com.google.Chrome/config/google-chrome/
NativeMessagingHosts/net.downloadhelper.coapp.json
VdhCoApp : VdhCoApp is ready to be used
```

Thunderbird

Aufbau der "profiles.ini"

```
flatpak install flathub org.mozilla.Thunderbird
```

Anschließend via Flatseal das Home-Verzeichnis zugänglich machen:



Oder alternativ:

```
cd ~
echo -e '[Context]\nfilesystems=home' >>
.local/share/flatpak/overrides/org.mozilla.Thunderbird
```

Nach der Installation einfach den .thunderbird Ordner aus dem Backup ins Home-Verzeichnis zurück kopieren.

Hibiscus



Konfig-Datei liegt unter: ~/.jameica.properties
Datensatz liegt unter ~/.jameica

Download direkt vom Hersteller: <https://www.willuhn.de/products/jameica/download.php>
Entpacken, jameica.sh starten ...

```
wget
https://www.willuhn.de/products/jameica/releases/current/jameica/jameica-
linux64-2.10.5.zip
```

```
unzip jameica-linux64-2.10.5.zip  
chmod +x jameica.sh  
./jameica.sh
```

Plugin Hibiscus installieren.

Threema

```
flatpak install flathub ch.threema.threema-web-desktop
```

Signal

```
flatpak install flathub org.signal.Signal
```

Telegram

Joplin

LaTeX

Adobe Reader

QOwnNotes

Nextcloud Client

Converseen

LibreOffice

```
flatpak install flathub org.libreoffice.LibreOffice
```

qpdfview



qpdfview habe ich durch **Okular** ersetzt

Angepasste Einstellungen:

Datei-Werkzeugleiste: openInNewTab, refresh, saveAn, print

Bearbeiten-Werkzeugleiste:

firstPage, currentPage, previousPage, nextPage, search, copyToClipboardMode, addAnnotationMode

Ansicht-Werkzeugleiste: scaleFactor, zoomIn, zoomOut,

continuousMode, twoPagesMode, originalSize, fitToPageWidthMode, fitToPageSizeMode, rotateLeft, rotateRight, fullscreen

Okular

```
flatpak install flathub org.kde.okular
```

Pinta

```
flatpak install flathub com.github.PintaProject.Pinta
```

XnView MP

```
flatpak install flathub com.xnview.XnViewMP
```

Entwicklung**FreeCAD**

```
flatpak install flathub org.freecad.FreeCAD
```

Prusa Slicer

Konfig-Pfad: ~/.var/app/com.prusa3d.PrusaSlicer/config/PrusaSlicer

```
flatpak install flathub com.prusa3d.PrusaSlicer
```

Visual Studio Code

```
flatpak install flathub com.visualstudio.code
```

Arduino 2.x

MQTT Explorer

```
flatpak install flathub io.github.Omniaevo.mqtt5-explorer
```

VirtualBox

Quelle: <https://www.virtualbox.org/wiki/Downloads>

```
wget  
https://download.virtualbox.org/virtualbox/7.2.0/virtualbox-7.2_7.2.0-170228~Debian~trixie_amd64.deb  
wget  
https://download.virtualbox.org/virtualbox/7.2.0/Oracle_VirtualBox_Extension_Pack-7.2.0.vbox-extpack  
sudo su  
apt-get install libqt6help6 gcc make perl linux-headers-amd64 linux-headers-6.12.41+deb13-amd64  
dpkg -i virtualbox-7.2_7.2.0-170228~Debian~trixie_amd64.deb
```

Wine32/64

```
sudo  
dpkg --add-architecture i386  
apt update  
apt install wine wine32 libwine:i386 fonts-wine
```

GUISrcpy

Um der srcpy oder per GUISrcpy auf ein Android Smartphone zugreifen zu können, muss bei diesem zuvor der Debug-Modus aktiviert werden. Dazu müssen die sog. Entwickleroptionen freigeschaltet werden. Soll der Zugriff nur über USB erfolgen, reicht die Freigabe von „Debugging über USB“ aus. Es geht drahtlos etwas komfortabler über WLAN mit „Debugging über WLAN“.

```
sudo su  
apt-get install adb  
exit  
flatpak install flathub in.srev.guiscrcpy
```

Multimedia

VLC



Konfig-Datei: ~/.var/app/org.videolan.VLC/config/vlc/

```
flatpak install flathub org.videolan.VLC
```

MediathekViewer



Konfig liegt unter:
~/.var/app/de.mediathekview.MediathekView/config/mediathek3/

```
flatpak install flathub de.mediathekview.MediathekView
```

gPodder

AviDemux

Asunder

RipperX

Audacity

EasyTag

MediaInfo

Gaming

Steam

From:
<https://www.von-thuelen.de/> - Christophs DokuWiki

Permanent link:
https://www.von-thuelen.de/doku.php/wiki/linux/debian_13_trixie/uebersicht?rev=1767375627

Last update: 2026/01/02 17:40

