

Telegram CLI auf Eingebetteten Systemen

Definition Eingebettete Systeme

Bei mir kommen die beiden Plattformen Raspberry Pi in unterschiedlichen Versionen und das System Cubietruck (aka. Cubieboard 3) zum Einsatz.

Quellen:

- [Telegram Homepage](#)
- [GitHub Project Homepage for Telegram CLI](#)
- [Patch, siehe unten](#)

Raspberry Pi B, Rev. 1

Vorbereitungen

Die folgenden Installationsschritte habe ich auf einem Raspberry Pi B Rev. 2 mit einem Raspbian GNU/Linux 9 (Stretch) durchgeführt.

```
sudo su
# notwendige Tools installieren
apt-get update
apt-get upgrade
apt-get install git libreadline-dev libconfig-dev libssl-dev lua5.2
liblua5.2-dev libevent-dev libjansson-dev libpython-dev make libssl1.0-dev
```

Sourcen von Git kopieren

```
git clone --recursive https://github.com/vysheng/tg.git

# In der Datei tgl/mtproto-utils.c, die Zeilen 101 und 115 auskommentieren.
Quelle [3]
# assert (0); // As long as nobody ever uses this code, assume it is broken.
# by
# //assert (0); // As long as nobody ever uses this code, assume it is
broken.
# (or delete the lines) and run make again.
```

Telegram CLI kompilieren

```
cd tg
./configure
```

make

Im Unterverzeichnis ./bin liegt dann das ausführbare Binary telegram-cli.

Cubietruck aka. Cubieboard 3

Cubietruck Informationen:

- <https://www.cubietruck.com/>
- <http://docs.cubieboard.org/>
- <https://linux-sunxi.org/Cubietruck>

Vorbereitungen

Die folgenden Installationsschritte habe ich auf einem Cubietruck aka. Cubieboard 3 mit einem Debian GNU/Linux 8 (jessie) durchgeführt.

```
sudo su
# notwendige Tools installieren
apt-get update
apt-get upgrade
apt-get install git libreadline-dev libconfig-dev libssl-dev lua5.2
liblua5.2-dev libevent-dev libjansson-dev libpython-dev make libssl-dev
```

Sourcen von Git kopieren

```
git clone --recursive https://github.com/vysheng/tg.git

# In der Datei tgl/mtproto-utils.c, die Zeilen 101 und 115 auskommentieren.
Quelle [3]
# assert (0); // As long as nobody ever uses this code, assume it is broken.
# by
# //assert (0); // As long as nobody ever uses this code, assume it is
broken.
# (or delete the lines) and run make again.
```

Telegram CLI kompilieren

```
cd tg
./configure
make
```

Im Unterverzeichnis ./bin liegt dann das ausführbare Binary telegram-cli.

Bedienung (allgemein)

Telegram im interaktiven Modus starten:

```
bin/telegram-cli -k tg-server.pub
```

Kontaktliste ausgeben:

```
./bin/telegram-cli -k tg-server.pub -e "contact_list"
```

eine Textnachricht versenden:

```
./bin/telegram-cli -k tg-server.pub -W -e "msg <EMPFÄNGER> \"Nachricht mit  
Leerzeichen\""
```

Installation

```
cd tg  
cp ./bin/telegram-cli /bin/  
mkdir /etc/telegram-cli/  
cp tg/tg-server.pub /etc/telegram-cli/  
telegram-cli -W -e "msg <EMPFÄNGER> \"Nachricht mit Leerzeichen\""
```

From:

<https://www.von-thuelen.de/> - Christophs DokuWiki

Permanent link:

<https://www.von-thuelen.de/doku.php/wiki/linux/messaging/uebersicht?rev=1586974936>

Last update: **2020/04/15 20:22**

